

tesa® 62856

Double-sided PE foam tape

PRODUCT INFORMATION

Product Description

tesa® 62856 is a double-sided tape consisting of a PE foam backing and a pure acrylic adhesive.

tesa® 62856 features especially:

- High ultimate adhesive strength for a secure bonding performance
- Conformable foam backing to compensate design tolerances or uneven surfaces
- High foam elasticity to level-out different thermal expansion of bonded parts
- Excellent temperature resistance performance
- Excellent converting properties

Main Application

- Permanent mounting of decorative exterior trims
- Permanent mounting of emblems, e.g. "candy bar" emblems
- Permanent mounting of bumper rails

Technical Data

■ Backing material	PE foam	■ Type of adhesive	pure acrylic
■ Colour	black	■ Elongation at break	400 %
■ Total thickness	1200 µm	■ Tensile strength	15.5 N/cm

Adhesion to

■ Steel (initial)	6.0 N/cm	■ Steel (after 14 days)	17.0 N/cm
■ ABS (initial)	5.5 N/cm	■ ABS (after 14 days)	17.0 N/cm

Properties

■ Temperature resistance short term	100 °C	■ Static shear resistance at 40°C	++
■ Temperature resistance long term	90 °C	■ Static shear resistance at 70°C	++
■ Static shear resistance at 23°C	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

Liner variants:
PV6 red MOPP (80 µm)

Peel Adhesion:
- after 14 days: foam splitting on Steel, ABS

For latest information on this product please visit <http://l.tesa.com/?ip=62856>

Page 1 of 1 / As of 03/21/15